




Technical data sheet

EGGER Skirting boards white

Application area

Installation of wall finishes after laying EGGER laminate and hybrid flooring.

Material data

Article	L201		Budget	Hamburg		Cubical			
	6 cm	8 cm	6 cm	7 cm	10 cm	4 cm	6 cm	8 cm	10 cm
Article No.	1818385	1525812	1279338	1036707	1036709	1483170	1483124	1483097	1483107
Profile drawing									
Length [mm]	2.400	2.400	2.400	2.400	2.400	2.400	2.400	2.400	2.400
Width [mm]	14	14	16	18	18	16	18	18	18
Height [mm]	58	80	58	70	100	40	60	80	100
PU [pcs]	10	5	8	8	6	10	10	8	6
PU [m]	24	12	19,2	19,2	14,4	24	24	19,2	14,4
PU dimensions [mm]	2.410 x 146 x 61	2.410 x 88 x 69	2.420 x 138 x 66	2.410 x 139 x 75	2.410 x 105 x 110	2.410 x 76 x 82	2.410 x 105 x 95	2.410 x 162 x 95	2.410 x 105 x 110
PU weight [kg] +/- 10 %	10,5	8,8	13,2	11,9	12,1	8,5	14,2	13,1	13,3
Pallet [pcs]	400	360	320	280	210	700	240	240	210
Pallet [m]	960	864	768	672	504	1.680	576	576	504
Pallet dimensions [mm]	2.450 x 800 x 670	2.450 x 800 x 763	2.450 x 800 x 659	2.450 x 800 x 660	2.450 x 800 x 690	2.450 x 800 x 710	2.450 x 800 x 710	2.450 x 800 x 610	2.450 x 800 x 690
Pallet weight [kg] +/- 10 %	471	685	579	468	472	639	391	442	516

PU = Packaging unit

General data

Surface	Impregnated decor paper
Colour	White (RAL 9016)
Light resistance	Level 7 (EN 20105)
Adhesive	Hot melt adhesive (Adhesive between carrier material and surface)
Carrier material	MDF (medium density fiberboard)
PEFC certificate	70 % (PEFC/06-38-171)
VOC and CH ₂ O emissions	A+ (ISO 16000 Teil 3,6,9,10)
Formaldehyde emission	E05 (EN 120)
Storage	- Store upright or lying flat on a level surface - Protect from direct sunlight and moisture - Climatic conditions: Temperature approx. 18 °C ; humidity 55–70%
Paintability	- Suitable for all commercially available acrylic paints and solvent-free paints - Prepare the surface properly before painting - Follow the paint manufacturer's instructions for use
Tolerances	- Cross-sectional dimensions: max. +/- 5 % deviation from nominal dimension permitted - Length dimensions: max. + 2 % / - 1 % deviation from nominal dimension permitted - Deformations: max. 2 % of the skirting board length and twists permitted
Mounting options	- EGGER Clipholder for invisible installation (only suitable for L201 6 cm and L201 8 cm) - Gluing (SMP mounting adhesive or 1K PU adhesive) - Nailing (pneumatic nailer)
Cleaning	- Use a vacuum cleaner with a dust brush attachment for cleaning - Clean with a cleaning agent with a pH < 8 and a damp cleaning cloth - Avoid liquid accumulation
Recycling	Recyclable
Disposal code	EWC: 17 02 01

Information

Only use adhesive tape with an adhesive strength not exceeding 2 N/cm (according to DIN EN 1939). We confirm that no paints, varnishes, lacquers, or adhesives containing organic solvents, biocides, or free formaldehyde are used or contained in the manufacturing process, in the preliminary products, or in the baseboards. All of the above values were determined under laboratory conditions and using defined laboratory setups and may differ from these test bench values when installed or when used with other system floor components. Tolerances are possible for all performance data mentioned due to methodological inaccuracies.

Provisional note

The information provided corresponds to the current state of knowledge and is intended solely for general product and application description. It does not constitute a guarantee of specific properties or suitability for specific applications. No legally binding claims can be derived from the information provided, and existing property rights must be observed. Technical content may be modified at any time due to possible further developments or changes in standards or legislation. The technical data sheet is therefore for information purposes only and does not replace binding instructions for use or a legal basis.