

CE Declaration of performance

according to Regulation (EU) No. 205 of the European Parliament and the Council of 9 March 2011

DOP Nr.:

DOP: 961

DOP: 966

1. Type:

EGGER Compact Laminate Flammex
CGF (Compact General – purpose Flame retardant) **Recipe 961**
ACF (Pearlescent laminate Compact Flame retardant) **Recipe 966**

Construction: - with flame retardant core layers
Construction: 800 with flame retardant underlay
2. Intended use:

Compact laminate panels/sidings for interior wall and ceiling finishes (including suspended ceilings)
3. Manufacturer:

FRITZ EGGER GmbH & Co. OG
 Weiberndorf 20
 6380 St. Johann in Tyrol
 Austria
4. Authorised representative:

not applicable
5. System of assessment and verification:

System 1
6. Harmonised standard:

EN 438–7 : 2005
- Notified body:

0766 Entwicklungs- und Prüflabor Holztechnologie GmbH (EPH)
 Zellescher Weg 24
 01217 Dresden
 Germany
- Certificate number:

Construction (-) **0766-CPR-634/1**
 Construction (800) **0766-CPR-687**

7. Declaration of performance:

Properties	Unit	Construction: -	Construction: 800
Thickness	[mm]	5 - 13	6 - 13
Density EN 323	[g/cm ³]	1,35	1,35
Bending strength EN ISO 178	[MPa]	80	80
Bending modulus of elasticity EN ISO 178	[MPa]	9.000	9.000
Release of formaldehyde EN 717-1	Class	E1, E1E05	E1, E1E05
Reaction to fire	Euroclass	B-s2,d0	B-s1,d0
Durability resistance to boiling water		pass	pass
Resistance to fixings	5 mm ≤ t < 6 mm	[N]	> 1.000
	6 mm ≤ t < 8 mm	[N]	> 2.000
	8 mm ≤ t < 10 mm	[N]	> 3.000
	t ≥ 10 mm	[N]	> 4.000

8. Technical documents

Construction: -

Classification report: **KB-Hoch-091094-8**

Testing laboratory: **NB 1508**

Construction: 800

Classification report: **L24/2672_06**

Testing laboratory: **NB 2397**

Signed for and on behalf of the manufacturer by:

Manfred Riepertinger

Head of Core Material Management
EGGER Group

(This document was created electronically and is valid without signature!)